

Model	Baęlantı	Giriş Debisi m3/saat – scfm	Voltaj	Toplam Aęırlık	Aktif Alümina kg	Boy mm	En mm	Yükseklik mm
MDA 130	1"	130 - 80	230/1/50-60	160	40	600	814	1312
MDA 185	1"	185 - 100	230/1/50-60	180	54	600	808	1566
MDA 250	1"	250 - 150	230/1/50-60	200	75	760	772	1580
MDA 300	1 1/2"	300 - 200	230/1/50-60	250	100	690	900	1558
MDA 360	1 1/2"	360 - 215	230/1/50-60	250	100	690	900	1558
MDA 440	1 1/2"	440 - 250	230/1/50-60	340	125	698	900	1759
MDA 575	1 1/2"	575 - 300	230/1/50-60	500	151	680	900	1991
MDA 680	2"	680 - 400	230/1/50-60	535	202	680	960	2216
MDA 850	2"	850 - 500	230/1/50-60	750	264	857	1016	2277
MDA 1000	2"	1000 - 600	230/1/50-60	755	357	1010	1075	2386
MDA 1250	DN80/PN16	1250 - 700	230/1/50-60	1000	404	1100	1294	2413
MDA 1500	DN80/PN16	1500 - 800	230/1/50-60	1050	454	1010	1300	2547
MDA 1800	DN80/PN16	1800 - 1000	230/1/50-60	1215	566	1110	1513	2479
MDA 2200	DN80/PN16	2200 - 1250	230/1/50-60	1550	708	1110	1460	2793
MDA 2700	DN80/PN16	2700 - 1500	230/1/50-60	1890	852	1252	1533	2831
MDA 3200	DN100/PN16	3200 - 1750	230/1/50-60	2240	954	1212	1653	3054
MDA 3600	DN100/PN16	3600 - 2000	230/1/50-60	2330	1070	1210	1653	3268
MDA 4400	DN100/PN16	4400 - 2500	230/1/50-60	3000	1436	1535	1905	2910
MDA 5000	DN150/PN16	5000 - 3000	230/1/50-60	3180	1670	1714	1843	3382
MDA 6300	DN150/PN16	6300 - 4000	230/1/50-60	3450	2016	1693	2114	3328
MDA 7200	DN150/PN16	7200 - 4500	230/1/50-60	3600	2446	1795	2518	3047
MDA 8800	DN150/PN16	8800 - 5000	230/1/50-60	3850	2906	1795	2518	3341
MDA 10800	DN200/PN16	10800 - 6000	230/1/50-60	4200	3354	1875	2583	3747
MDA 12500	DN200/PN16	12500 - 7360	230/1/50-60	6470	3894	1935	2545	4175